


3 mil UV stabilized, pre-perforated clear PVC laminating film with a matte finish, coated on one side with a heat activated solvent acrylic adhesive that is protected by a moisture stable bleached Kraft gridded release paper coated on one side with siliconized PE.

Specifications

Face Material	Matte Perforated PVC
Color and Finish	Matte
Adhesive	1 mil Solvent Acrylic (Heat Activated)
Liner	1 Side PE Coated Bleached Kraft Grid Paper (Moisture Stable)
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Service Temperature Range	-4°F to 203°F
Shelf Life	2 years @ 59°F to 72°F; 50 - 55% Relative Humidity
Outdoor Durability	Not Applicable

Ordering

Catalog #	Width (in)		Length (ft)
0440550P	51"	x	300'



Applications

- Fine art prints
- Photographic prints
- Gallery and museum framing
- Exhibition graphics
- Plaque finishing and mounted display

Features and Benefits

- Matte, non-glare finish reduces reflections for clearer viewing in bright lighting.
- Durable surface protection helps guard prints against scuffs, scratches, and handling damage.
- Heat-activated adhesive creates a strong, reliable bond when applied with a heat press.
- Professional matte finish enhances presentation for framed and display graphics.

Contact us!

- 📞 [800-552-9427](tel:800-552-9427)
- ✉️ info@qmls.com
- 🌐 www.qmls.com

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.