

DuraVinyl 258



DuraVinyl 258 is a self-adhesive vinyl with a high opacity monomeric PVC film. Equipped with a high performance removable adhesive clay coated double PE embossed paper liner.

Specifications

| | |
|-----------------|--|
| Base Material | White soft calendered PVC, with superior opacity |
| Adhesive | Clear acrylic base, removable bubble free |
| Thickness | 4 mil vinyl with air release removable adhesive |
| Fire Resistance | ISO 13501-1 / ISO 11925-2 |
| Opacity | 98% |
| Applications | <ul style="list-style-type: none">• Best suited for short-term advertisements on finished surfaces that are flat, smooth and clean• Great option for window graphics due to its opacity and clear air egress adhesive |

Ordering

| Catalog # | Width (in) | | Length (ft) |
|-----------|------------|---|-------------|
| 0925854 | 54" | x | 150' |



Paired with our premium laminates in matte, luster, or gloss.



Learn about our laminates!



[Click Here](#)

Durability

- Durability up to 4 years
- Shelf life 24 months (stored at a temperature of 20°C± 5°C and 50% ± 5% relative humidity)
- Do not expose to direct sunlight or heat sources
- The product must be stored vertically, so that its quality is not compromised

Printer Settings

Since the migration of the plasticizer affects the quality of the latex print, this guarantees it for 6 months. After that date, the material must be used in solvent, eco-solvent and UV printing. It must also be protected with the recommended lamination in order to provide the necessary strength. For the best possible print quality, please make sure you are using the correct print profiles.

Printing Platforms:

- Specially developed for solvent, eco-solvent, UV and UV gel on large format printing.



Non-vertical application results in a significant reduction in durability, as well as climate and angles of sun exposure. It is recommended that the vinyl remains at least 25 hours at the temperature of the workplace before it is used.



Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.