

DuraVinyl 352



DuraVinyl 352 is a 6.0-mil matte white semi rigid vinyl featuring an ultra low-peel removable adhesive that is designed for various applications.

Specifications

Face Material	6.0-mil semi rigid vinyl
Color and Finish	Matte white
Adhesive	00, low-peel, microsphere removable
Liner	90# polycoated bleached layflat
Minimum Application Temperature	50°F
Service Temperature Range	-40°F to +180°F
Shelf Life (73°F)	1 year
Outdoor Durability	Up to 5 years

Ordering

Catalog #	Width (in)		Length (ft)
0935254	54"	x	150'
0935260	60"	x	150'



Paired with our premium laminates in matte, luster, or gloss.



Learn about our laminates! 

Ask sales rep!

Features and Benefits

- Removable adhesive – we recommend removing graphic at a 180° from the wall, not 90°, to help reduce the chance of any adhesive transfer or wall damage*
- Microsphere removable acrylic adhesive
- Compatible with a variety of printing methods including solvent, eco-solvent, latex, UV ink jet and conventional and UV screen.
- Recommend leaving a ¼-inch border around your graphic when printing.
- Recommend at least 24 hours of cure time before cutting.
- Removable for up to one year under normal interior conditions.

Applications

- Wall graphics
- Point of purchase displays
- Trade show displays

*Removing wall graphics can cause damage to walls due to a variety of uncontrolled variables. QMLS does not warrant damage to interior wall surfaces caused by the removal of wall graphics even if a removable adhesive is used.



 **800-552-9427**
 **info@qmls.com**
 **www.qmls.com**

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.