

Gallery Bond



Gallery Bond is a 3 mil unsupported pressure sensitive adhesive wound on a single poly-coated release liner. It is formulated for demanding applications such as bonding to low surface energy substrates.

Specifications

Adhesive	3 mil clear unsupported acrylic
Liner	5.5 mil polycoated kraft
Laminating Temp	68° F to 100° F
Shear (1 kg)	72° F, 85+ Hours to Fail
Peel Adhesion 2 mil PET backed	8.5 LBS (30 mins) 9.9 (24 hour)
Service Temperature	Application: Above 50° F (10° C) for best performance End Use: -40° F to 300° F (-40° C to 149° C)
Shelf Life	Two-year shelf life when stored at 75° F. (24° C.) and 50% relative humidity or less. It is recommended that the product be stored in its original package until ready to use.

Ordering

Catalog #	Width (in)		Length (ft)
0470554	54"	x	100'

Gallery Bond is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery.

To place an order, email us at info@qmls.com or call us at 1-800-552-9427.

Features and Benefits

Gallery Bond is used to adhere a board (typically DiBond) to the back of an acrylic face mount to sandwich the print between the two boards.

- Can be used wherever a high coat weight adhesive is required
- Bonding to slightly textured surfaces
- Quick initial tack
- High peel and shear properties
- Excellent service temperature range
- Conformable with good dimensional stability

Application Details

For best performance surfaces must be clean, dry and free of any oil, grease or other contaminant.