

# HardGuard Light Stopper



A 10 mil 100% opaque white, low-melt, thermal laminating film. Features a special light-blocking foil between its adhesive layers. Designed for use as a backing film for top-quality posters, tradeshow graphics, and POPs where high opacity and rigidity are required.

## Specifications

Guage	9.5 mil (87.3lb) polyester Test method ASTM D 645
Primer	0.75 mil (11.3 lb) white extrusion coating 0.30 mil (12.6 lb) foil 4.40 (71.9 lb) white coextrusion
Yield	2,360 in/lb
Opacity	0% transmission Test method ASTM D 1003
PET Side Coefficient of Friction	0.40 Test method ASTM D 1894
Heat Seal Initiation Temp	170°F @ 40psi, 0.5 sec dwell
Useable Temperature Range	170°F to 245°F

## Ordering

Catalog #	Width (in)		Length (ft)
0880335	38"	x	250'
0880350	51"	x	250'

### Storage:

New rolls: 50° to 86°F, 35 to 65% RH.  
Open rolls: Cover rolls with plastic bag, use end cap if storing on end. Do not stack rolls. Allow material time to adapt to room conditions.

These products are manufactured without the use of CFC's or VOC's.

## Applications

HardGuard Light Stopper was designed for use as a backing film for:

- Top-quality posters
- Tradeshow graphics
- POP

It is also suited for rollable graphics and match mural displays. Combine it with HardGuard Clear Texture to ensure the end product stands up to the rigors of tradeshow applications