

InstaShield Poly Matte

InstaShield Poly Matte is a 3 mil, high quality, non-PVC matte overlaminate with an hi-bond adhesive.

Uses

- Ideal for protecting graphics for use on flat surfaces.
- Non-PVC Applications

Advantages

- Provides a non-glare, scratch resistant surface.
- Will not silver or cause a clouded effect.

Performance Guidelines

- Laminate with heat at least at 122°F and run laminator at a slower setting at full pressure.
- Printed materials must be properly dried before applying the lamination.
- Ideally, the lamination should be allowed to cure for 24 hours before trimming.
- When rolling up the graphics, roll with the laminate side on the outside on a 3" core.
- Before installing the film, it is recommended to allow the graphics to become acclimated to the temperature of where they will be installed for at least 24 hours.
- Application Temperature >50°F
- Service Temperature 14°F to 158°

Specifications

Base Material	3 mil flexible polypro
Finish	Matte Clear
Adhesive	Permanent acrylic adhesive
Liner	2 mil Glassine
Outdoor Durability	3 Years
Storage	Store Vertically
Shelf Life	2 Years at 73°F, 50% RH

Ordering

Catalog #	Width (in)		Length (ft)
0580060	60"	x	150'

InstaShield Poly Matte is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery.

To place an order, call us at **1-800-552-9427**.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products