

# **Quality Performance Matte Laminate**

## **Quality Performance Matte Laminate**

Durable 3 mil PVC laminate with UV protection and clear high-tack adhesive — no hazing or silvering.



#### Uses

- · Ideal for short-term
- Flat surfaces
- · Indoor and outdoor



### Advantages

- Adhesive: Eco-friendly, clear, high-tack for UV/Latex prints
- Film: Certified PVC, matte finish
- Protection: Scratch-resistant, long-lasting, enhances color
- · Pressure sensitive
- · Conformability around UV ink



Fire resistant



#### **Size**



## Catalog #

54" x 150' 0489154 60" x 150' 0489160



## **Ordering**

Quality Performance Matte Laminate is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery.

To place an order, call us at 1-800-552-9427.



## **Specifications**

| Face Material                      | 3 mil PVC with UV<br>Protection   |
|------------------------------------|---|
| Finish                             | Clear Matte   |
| Adhesive                           | Permanent High Tack   |
| Liner                              | 2 mil Glassine  |
| Durability                         | Up to 4 Year Outdoor  |
| Storage                            | Unboxed rolls suspended horizontally through the core. Rolls in shipping cartons stored horizontally. |
| Shelf Life                         | 70°F and 50% relative<br>humidity   |
| Lamination Type                    | Cold Lamination   |
| Minimum Application<br>Temperature | 40°F  |
| Service Temperature                | -40°F to 180°F  |



## **Performance Guidelines**

- Adhesion to stainless steel: 48 oz/in, based on PSTC-1 testing after a 24-hour dwell time at 70°F and 50% relative humidity.
- Run heat at 125°F to reduce silvering.
- Values are typical and may vary.
- Conduct thorough testing before full use.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.