



WindowBond

WindowBond

WindowBond is a 2 mil clear film with a permanent adhesive on one side and a removable adhesive on the other. It features an embossed release liner, which forms slight grooves in the adhesive allowing air to escape on installation. The result is a visually clear bubble free application.

Uses

Window graphics, interior mounted wall graphics. WindowBond is Quality's premier product for hand applications of graphics to windows and glass.

Advantages

The micro grooves in the removable adhesive make mounting the image easy using a squeegee or burnishing pad - no bubbles, no wrinkles, and no need for a wet application. The image can be repositioned up to 10 times without compromising the micro grooves.

Size	Catalog #
51" x 164'	0473070
54" x 164'	0473080

Instructions for Use

1. Ensure windows are cleaned thoroughly with soap and water. Do not use ammonia based cleaners.
2. Laminate the permanent adhesive to the face side of the image.
3. Remove embossed release liner and apply by hand with a squeegee, exerting minimum pressure.
4. The micro grooves incorporated into the adhesive layer allow air to evacuate during installation, assuring an easy, bubble-free installation.
5. The image can be repositioned up to 10 times without compromising the micro grooves.
6. Allow the image to cure for 24 hours to dissipate any slight silvering.

Specifications

Film Carrier	Clear PET
Adhesive	Permanent solvent acrylic one side, removable, ph neutral, aqueous one side
Initial Tack	High/ Moderate
Application Temperature	65°F to 120°F
Application Speed	1' to 6' per minute for the permanent side using a roller laminator.
Release Liner	Moisture-stable paper (100 gsm) on permanent side. Filmic textured release liner with blue grid on removable side.
Outdoor Durability	Indoor use only.
Service Temperature Range	30°F to 90°F
Storage Conditions	50-85°F, 40-80% RH. Store in original packaging.
Shelf Life	One year from ship date when stored in proper conditions.

Ordering

WindowBond is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.