



Ultima® Pro FL - 13 oz.



Technical Data Sheet Ultima® Pro FL - 13 oz.

Ultima® Pro 13 oz. FL Matte is a smooth, versatile 13 oz. front-lit banner material. The material has a unique construction making it ideal for outdoor banner and truck-side applications. Ultima Pro 13 oz. FL Matte provides an excellent option for printers looking for a strong, high quality, cross-functional substrate. Ultima Pro Matte FL is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. Available in widths from 38" - 196".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN60001	100% PES	100% PES
Yard dtex	High Tenacity Yarn 100% PES	1100 x 1100 dtex	1000 x 1000 denier
Type of Coating	N/A	PVC	PVC
Total Weight	N/A	440 g/m ²	13 oz/yd ²
Tensile Strength	DIN53352 B53424	2000 x 1800 N/5cm	228.40 x 205.56 lbs/in
Tear Strength (warp/weft)	DIN53356 B53424	270 x 230 N	60.70 x 51.71 lbs
Flame Resistance	NFPA701, Title 19, CSFM		
Low Temperature (No Crack at:)	DIN53357 BS3425 Method 9B	-20°C	-4°F
RF Weldable (Heat Sealable)	Yes		

Applications

	Boulevard Banner	Banner	Billboard	Tradeshow Graphics	Building Graphics	Display Systems	Truckside (Clip-In)
Applications	■	■	■	■	■	■	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing
■	■	■	* ■	■

*Certified for HP Latex Inks

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.52, 2.50, 3.20, 5.00	38", 54", 63", 98", 126", 196"

Information provided here is based on research and is believed to be reliable as of printing date. The information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451