



## **Description:**

Texwalk Canvas is a printable, fabric reinforced PVC for indoor smooth wall and decal applications and short-term outdoor wall applications. It is easy to apply and remove and leaves little to no adhesive residue. It has a canvas finish, sticks to almost any indoor wall surfaces and can be cut into any shape.

# **Applications:**

- Short or long term indoor walls
- Short term outdoor walls
- Point of purchase retail graphics
- Decals

### **Advantages:**

- · Can be butt seamed for wallcovering applications
- Durable surface does not require laminate
- Can be kiss cut
- · Little to no adhesive residue
- Sticks on almost any smooth surface
- UV, Latex, and Eco Solvent printable

### **Technical Information:**

Rolls: 48"x 82' (1.22m x 25m) Product: 12 mil fabric reinforced vinyl Finish: Canvas texture Adhesive: Repositionable, solvent acrylic adhesive Liner: 78lb Type I wall covering for CCC-W-408D Class A for ASTM E-84 Shelf life: 1 year, 2 years if stored in controlled environment Durability:

- 36 months indoor vertical surfaces
- 4-6 months as an indoor floor decal
- 1-3 months on smooth outdoor surfaces

### **Printing Method:**

TexWalk Smooth is inkjet printable via solvent, eco-solvent, uv-curable or latex inks. Application surface must be dry, clean and above 50°F before application. For most printers, choose "generic self adhesive vinyl setting" for best results.

#### Storage:

It is recommended to store the product in closed packaging at a temperature of  $+60^{\circ}$ F to  $+85^{\circ}$ F ( $+15^{\circ}$ C to  $+30^{\circ}$ C) and humidity range of 45% to 60%. The product has a shelf life of 24 months.

Size	Catalog #
23" x 10'	AA-WALL01-TC3
48" x 82'	AA-WALL01-TC



Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.

www.qmls.com 800/552-9427 info@qmls.com fax 203/281-6451