



TexWalk Smooth

Applications:

Texwalk Smooth is a printable, fabric reinforced PVC for indoor smooth wall and decal applications and short-term outdoor wall applications. It is easy to apply and remove and leaves little to no adhesive residue. It has a smooth finish, sticks to almost any indoor wall surfaces and can be cut into any shape. It can be used for indoor floor graphic applications (carpet, tile, wooden and PVC floors and untreated stone) with an appropriate slip rated laminate.

Advantages:

- Will not shrink - Can be butt seamed
- Matte finish
- Can be kiss cut
- Can be laminated with pressure sensitive laminate
- Durable surface - does not require laminate
- Little to no adhesive residue
- Sticks on almost any smooth surface
- UV, Latex, and Eco Solvent printable

Technical Information:

Rolls: 48"x 82' (1.22m x 25m)

Product: 12 mil fabric reinforced vinyl

Finish: smooth Matte

Adhesive: Repositionable, solvent acrylic adhesive

Liner: 78lb

Type I wall covering for CCC-W-408D

Class A for ASTM E-84

Shelf life: 1 year. 2 years if stored in controlled environment

Durability:

- 36 months indoor vertical surfaces
- 4-6 months as an indoor floor decal
- 1-3 months on smooth outdoor surfaces

Printing Method:

TexWalk Smooth is inkjet printable via solvent, eco-solvent, uv-curable or latex inks. Application surface must be dry, clean and above 50°F before application. For most printers, choose "generic self adhesive vinyl setting" for best results.

Storage:

It is recommended to store the product in closed packaging at a temperature of +60°F to +85°F (+15°C to +30°C) and humidity range of 45% to 60%. The product has a shelf life of 24 months.

Size	Catalog #
23" x 10'	AA-WALL01-TS3
48" x 82'	AA-WALL01-TS



Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products.