



panoRama TwoWay Vision

A unique, clear PVC film embedded with a white prism technology.

Don't let your branding to get lost in the dark! The white prism technology transmits ambient light through the film for vibrant day-to-night window graphics.

Create stunning window graphics, viewed from both sides of the window, without the need for white ink.

www.qmls.com

APPLICATIONS

- Retail Store Fronts
- Corporate Environments
- Restaurants
- Flat and Slightly Curved Glass

panoRama Two Way Vision

MATERIAL

Face Film	Printable Clear (30%)/White (70%) Calendared PVC with Integrated White Prism
Back Side	Clear/White
Adhesive	Removable Clear Solvent Acrylic
Liner	Siliconized Paper – 7 mil (180µ +/-10µ)
Film Thickness	5 mil (120µ +/-10µ)
FR Certification	Not Tested

DURABILITY

Interior	Up to 3 Years
Exterior	Up to 2 Years - Vertical Exposure under Normal Conditions
Environment	Humidity & Solvent Resistance – Very Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 77°F (+15°C to +25°C) and Relative Humidity between 45% to 75%
Repositionable	Yes – During Initial Installation

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	-14°F to +122°F (-25°C to +50°C)
Removability	Clean Removal with No Adhesive Residue, up to 6 Months - Adhesion May Increase over Time
Removal Temp	+50°F (+10°C) or Greater
Exclusions	NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. ALWAYS clean and dry glass surface prior to application.

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex



Material Sizes

- 54" x 100'



Advantages

- Embedded White Prism Transmits Ambient Light for Vibrant Translucent Window Graphics Both Day and Night
- No White Ink Needed
- Excellent Durability for Interior or Exterior Installations without Lamination
- Clean Removability (Up to 6 Months Without Residue)

→ For more information

For additional product information, performance, and warranty guidelines please contact Quality Media and Laminating Solutions. 800-552-9427 • www.qmls.com