

# DURAPRINT DUO

#### **Product Description**

Double-sided bright white matte top coated polypropylene with blockout to produce 2-sided prints. This is the perfect Non PVC solution for trade show displays, posters, double sided window graphics (using our Windowbond, PromoBond, or EzBond) Compatible with eco solvent, latex and UV inks.

#### Uses

- Low Cost Roll-up Displays
- · Banner Stands
- POP-In Displays
- "Push-Pull" Window Signage
- Trade Show Displays
- Hanging Signs

#### **Advantages**

Duraprint is the perfect solution for two sided graphics with the added bounus that is polypropylene and non-PVC. Duraprint Duo 99% opacity blocks out light from bleeding through to the back graphic. it's 11mil thickness makes applying it to windows with a Quality ahesive like Windowbond, Promobond or Ez Tack much easier.

## **Finishing Mounting Section**

Lamination may not be required for some applications. Pressure sentitive laminates like Quality Value or Production Lustre will extend the life of the graphic. Pressure sentitive adhesive like Viewbond are recommended for 1st surface and 2nd surface mounting applications. Our line of pressure sensitive window adhesives can be used to create opaque, two-sided inside mount window graphics

### **Specifications**

Surface Finsh: Matte Base Material: Polyroplene Base Weight: 220 GSM +/-10%

Caliper: 11 Mil +/-1

Brightness: 90(ISO Blue Whitness)

Whiteness: 93(CIE Ganz)

Gloss Measurment: 13 +/- 10% by angle of 60

Opacity: 99

Durability: Indoor Up to 1 year Outdoor: 6 months

Roll Length: 100 Ft Roll Widths: 36" & 60"

Core: 3"

Print SIde: Both SIdes

#### Size Catalog #

Size	Catalog #
36" x 100'	6636
60" x 100'	6660

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products

Phone: (800) 552-9427 | info@gmls.com | www.gmls.com