

Product Description

Gloss white; gray backed cast vinyl with permanent adhesive and a polycoated layflat liner for long term installation on coarse wall surfaces. The film is a premium high performance, flexible cast vinyl for application to irregular surfaces. Latex, solvent, eco-sol and UV ink jet printable.

Uses

- Rough surfaces such as brick walls
- Fleet graphics
- Building wraps
- Decals

Advantages

- Flexible, high quality, cast vinyl is ideal for applications with rough or irregular surfaces
- 10 year outdoor durable gloss white flexible vinyl
- Permanent adhesive features block out primer

Ordering

DuraVinyl 704 is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

| Size | Catalog # |
|------------|-----------|
| 54" x 150' | 0970454 |
| 60" x 150' | 0970460 |

Specifications

| | |
|---|---|
| Film Caliper | 2 mil |
| Adhesive | Permanet solvent |
| Release Liner | 90# polycoated layflat |
| Outdoor Durability | 10 years |
| Minimum Application Temperature | 40°F |
| Service Temperature Range | -50°F to +200°F |
| Adhesion Values | 20 min. 24hrs. (Stainless steel substrate 180° peel @ 10"/min, 73° F) 45 oz/in 60 oz/in |
| Shelf Life | 1 Year @ 73°F, 50% RH |
| Elongation | 120% |
| 60° Gloss | 80 minimum |
| Dimensional Stability (48 Hrs. @ 150° F) | 0.01 in. |
| Installation Information | Surface Prep - Wire brush the surface to remove any loose rocks / pieces of the wall. Do not use water. Heat and roller brushes should be used to apply DuraVinyl 704 into the valleys of rough surfaces. Edge sealer is recommended for installations of this product. |
| Removal Information | Always use heat and remove the graphic by pulling 3" off top and pulling straight down |

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products