

Product Description

Fusion Display Film is a polyester film with a satin textured surface. The polyester base film has a grayback blockout and is stable and will lay flat. The textured surface has a PVC print surface that makes this product a competitively priced solution when compared with traditional polyester display films.

Applications

- Pop Up and Roller Banner Stands
- POP Displays
- Signage and Advertising

Advantages

- Recommended for solvent and latex printer
- Compatible with UV curable printers
- Designed to resist heat from latex printers
- Anti slip/static coating provides accurate printer feeding.
- Will not curl (highly stable)
- Can be used indoors and outdoors.
- One step process - No laminate required.

Ordering

Fusion Display Film is a Quality Media and Laminating Solutions exclusive product. It's stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427

9 Mil Size

Catalog #	Width (in)		Length (ft)
183609	36"	x	100

12 Mil Size

Catalog #	Width (in)		Length (ft)
183612	36"	x	100
184212	42"	x	100
186012	60"	x	100

Specifications

Film	Polyester/PVC Print Surface
Finish	Satin
Thickness	9 / 12 mil
Application Temperature	60°F to 86°F
Storage Temperature	50°F to 70°F, 30-50% RH

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products