CONTINENTAL



iTacGreen / iTacGreen Plus 🗘

A multi-layered cast, polypropylene film featuring a proprietary long-term removable, washable, reusable adhesive.

Great for any smooth surface, and can be laminated with ProtectWalk to create reusable floor graphics.

iTacGreen and iTacGreen Plus are a sustainable alternative to PVC films.

www.qmls.com

APPLICATIONS

- Temporary Vehicle Graphics
- Superb Counter Mat Material
- Elevator Graphics
- Short-Term Graphics on Granite, Marble, and Polished Stone
- Temporary Dance Floor/Event Graphics



iTacGreen / iTacGreen Plus 🛟



MATERIAL	
Face Film	Printable Biaxially-Oriented Polypropylene
Back Side	Opaque Silver Metallic
Adhesive	Proprietary Long-Term Removable Repositionable Reusable
Liner	Clear PET - 5 mil (125µ +/-10µ)
Film Thickness	3 mil (75 μ +/-10 μ)
FR Certification	Not Tested

DURABILITY	
Interior	Up to 4 years
Exterior	Up to 3 Years - Vertical Exposure under Normal Conditions.
Environment	Humidity & Solvent Resistance – Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 68°F (+15°C to +20°C) and Relative Humidity between 45% to 70%
Repositionable	Yes - Highly

APPLICATION/REMOVAL		
Application Temp	+50°F to +86°F (+10°C to +30°C)	
Service Temp	+0°F to +122°F (-17°C to +50°C)	
Removability	Cleanly Removable with No Adhesive Residue - Adhesion May Increase Depending on Surface and Length of Time	
Removal Temp	+50°F (+10°C) or Greater	
Exclusions	NOT to be Applied to PVC, Copper, or Unpainted Metal, as the Application May Become Permanent	

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean with a mild detergent and water and dry thoroughly. ALWAYS clean and dry glass surface prior to application. iTacGreen and iTacGreen Plus are not designed for structured surfaces. For full installation and removal recommendations, please refer to "iTacGreen Installation Recommendations".





Printing Methods

- · iTacGreen: Digital UV & Latex; Screen Print; Offset
- · iTacGreen Plus: Digital: Solvent, Eco-Solvent, UV, & Latex; Screen Print; Offset



Material Sizes

- 54" x 100'
- 54" x 50'



Advantages

- Easy Application on Smooth Surfaces and Removal with No Residue
- · Washable, Reusable Adhesive Means Graphics May Be Used Again and Again Without Loss of Adhesion
- · Laminate with ProtectWalk for Non-Skid Floor Graphics



For more information

For additional product information, performance, and warranty guidelines please contact Quality Media and Laminating Solutions. 800-552-9427 • www.qmls.com



^{*}For critical substrates and all surfaces, please test PRIOR to application.