

Instashield FG

Instashield FG is a 5 mil, low-glare, rigid vinyl film formulated for floor graphics.

Uses

Combined with Duravinyl Matte or Self Adhesive Matte Instashield FG creates durable, high-quality floor graphics with a textured finish for protection and slip resistance. It offers an economical alternative to Instashield Polycarbonate and, unlike some competing products, features an easy-to-use pressure sensitive adhesive.

Ordering

Instashield FG is a Quality Media and Laminating Solutions exclusive product. It is stocked in all of our distribution centers and available for immediate delivery. To place an order, call us at 1-800-552-9427.

Size	Catalog #
25" x 150'	0500225
38" x 150'	0500238
51" x 150'	0500250
54" x 150'	0500254

Specifications

Film	Matte clear scuff resistant semi-rigid vinyl
Adhesive	Permanent acrylic
Liner	Polyester
Thickness	Film = 5 mil Adhesive = 1.2 mil Liner = 1.5 mil
Processing Range	50° to 90°F
Min Application Temp	50°F
Servicable Temp Range	-40°to +180°F
Flammability	Self Extinguishing
Chemical Resistance	Resistant to water, mild acid, salt, alkalis, oils, aliphatic solvents
Outdoor Durability	2 years
Shelf Life	2 years at 73°F

Floor Graphics Instructions

Compatibility – Designed to be applied to smooth, indoor floor surfaces in good condition, including waxed commercial PVC and ceramic tile. This product should not be laminated to any product that contains migrating plasticizers.

Substrate Condition – Floor surface must be clean and dry. Any wax, paints, or coatings on surface must have good adhesion to flooring substrate. Wait 7 days before applying decal to newly painted surfaces.

Applications Instructions – Peel back about 1" of the release liner from top of graphics. Fold and crease liner back. Position graphics starting with top of graphics. Apply firmly using plastic squeegee. Continue removing liner and smooth out graphics with squeegee. After entire graphic is applied, squeegee entire decal, working from the center out, to remove any air bubbles and to ensure good adhesion. Make sure edges are applied well. Product should not be applied using wet method.

Maintenance – Wait 24 hours after application before cleaning or waxing floor. To ensure condition of graphic avoid exposing to heavy equipment traffic.

Cleaning – Clean scuff marks by rubbing with tennis ball. If that does not work, use alcohol isopropyl.

Removal – Lift one edge of graphic and pull using short quick strokes.

Disclosure: Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality Media will not be held responsible for customers end use of product. Quality Media is available for directions and advice as to proper use and application of our products