

PROTECT Outdoor Laminate

G-061SV30 Gloss M-062SV30 Matte

PRODUCT DESCRIPTION:

PROTECT Outdoor is a 1.2 mil clear film laminate that offers excellent clarity, dimensional stability, and long-term outdoor durability. Designed for 5+ year outdoor surface protection of printed films and substrates.


TYPICAL APPLICATIONS:

Architectural window decorations, window graphics, transit glass & windows, outdoor signage.

FILM CHARACTERISTICS

UV Light blocking, flame resistant, anti-graffitti properties (cleanable with IPA or mineral spirits), self cleaning (very low surface energy), thin & conformable, gloss is optically clear.

PERFORMANCE:



Facestock: 1.2 mil clear film with outstanding outdoor durability. Offering excellent dimensional stability combined with good solvent, elevated temperature, and UV resistance.

Adhesive: Ultra clear permanent acrylic adhesive has excellent chemical, humidity, and temperature resistance. Wet apply recommended for window applications.

Liner: 2 mil clear polyester release liner designed to ensure adhesive smoothness and preserve the films optical clarity.

	GE	NERAL CHA	RACTERISTICS	
Properties	Typical Values Film Adhesive Liner		Unit of Measure 1.5 mil ± 10% 1 mil ± 10% 2 mil ± 10%	Test Method
Physical				
Peel Adhesion Stainless Steel	30 Minutes 12.8	24 Hours 14.5	N/25mm @ 72°F , 50% RH	Lintec Method
UV Blocking	98%		UV Light Blocking	
Dimensional Stability	Excellent		Inches	FTM 14
Outdoor Durability	Up to 5 Years		Years	Vertically Applied
Minimum Application Temperature	+40°F			
Service Temperature Range	-10°F to +275°F			

The statements in this technical information are based up on our knowledge and practical experience. This data is intended only as a source of information, and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible applications, customers should determine the suitability of this material for their specific purpose prior to use.

© 2024 Lintec of America, Inc. All rights reserved.



935 National Parkway

Suite 93553 Fax: 847.229.0548

Schaumburg, IL 60173 Web: www.digitalwindowgraphics.com

Tel: 847.229.0547

Toll Free: 800.806.8977